



## BZ-110A wetting and dispersing additive

**Composition:** polyphosphate modified special compound

**Appearance:** yellow transparent liquid

**Active ingredient:** 45%

**Solvent:** Xylene

**Application scope:** wood coatings, automotive coatings, coil coatings, industrial coatings, inks

**Recommended dosage:** Inorganic pigment 5-10%; organic pigment 10-20%; carbon black 20-50%.

**Method:** It is recommended to dissolve the dispersant completely in the grinding medium first, and then add the pigment to grind.

### Characteristics and advantages:

Excellent wetting effect, good dispersing effect on titanium white, red, blue, green, reduce the grinding time of pigment, prevent pigment flocculation, not easy to return to coarse.

It has good resin compatibility, can reduce viscosity and provide mobility, improve coloring strength.

It has stable dispersion of pigment in epoxy system, and is suitable for the preparation of pigment concentrated slurry.

**Package:** 25KG non-recycled blue plastic drum.

Before the product is completely empty, the lid should be tightly closed after use.

**Storage:** Keep away from heat and light source and keep away from light.

**Caution:** Please carefully evaluate the relative usage amount before use.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statement is for reference only.

The company does not assume any legal responsibility, please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.