



BZ-20000 Dispersant additive

Composition: polymer

Appearance: light yellow transparent liquid

Active ingredient: 100%

Solvent: None

Application scope: Industrial coatings, automobile coatings, plastic paints, epoxy coatings, inks, etc.

Recommended dosage: Inorganic pigment: 2-5%; Organic pigment: 10-20%; Carbon black: 30-80%.

Usage:

In order to get the full effect, the additives must be added into the abrasive first, and then the pigments are put in. Pre-mix the resin and solvent components in the abrasive, then add the additives slowly with stirring, and only when the additives are fully dispersed can the pigments be added. Please test the appropriate dosage before use.

Characteristics and advantages

- 1、 Improve the wettability of pigment, increase the adding amount of pigment in pigment concentrates, improve the color spreading of pigment, and have efficient dispersion performance and excellent storage stability.
- 2、 It has excellent grinding and dispersing effect on carbon black and organic pigment; it is widely used in various systems of ink, especially for gravure printing, silk screen printing, UV silk screen printing ink, PVC ink.
- 3、 It has outstanding dispersing effect on alcohol soluble and alcohol water soluble, solvent type color paste, color paste, color flake, and it has very good viscosity reduction effect.

Package: 25KG non-recycled blue drum.

Before the product is completely empty, the lid must be tightly closed after use.

Storage: Keep away from heat source and light source and keep away from light.

Precautions: Please carefully evaluate the relative usage amount before use.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statement is for reference only.

The company does not assume any legal responsibility, please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.