



## BZ-2193 epoxy dispersant additive

**Composition:** Polyester modified special compound

**Appearance:** light yellow transparent liquid

**Active ingredient:** 40%

**Solvent:** Xylene

**Application scope:** industrial coatings, can coatings, epoxy coatings, etc.

**Recommended dosage:** titanium dioxide: 5-6%; organic pigment: 10-20%; carbon black: 30-50%;  
to the full amount: 0.3-1.5%.

**Usage:** In order to get the full effect, the additives must be added to the abrasive first, and then put into the pigment. Pre-mix the resin and solvent components of the abrasive, then slowly add the additives with stirring, and only when the additives are fully dispersed can the pigments be added. Please test the appropriate dosage before use.

### Characteristics and advantages

Good resin compatibility, good wetting and dispersing effect for titanium white, red, blue and green of epoxy system.

Pigment dispersion stability is good, not easy to return to the coarse, suitable for the preparation of pigment concentrates.

**Package:** 25KG non-recycled blue pail.

Before the product is completely empty, the lid should be tightened after use.

**Storage:** Keep it away from heat and light source and keep it away from light.

**Precautions:** Please evaluate carefully before use, suitable for matte furniture paint, also can be applied to glossy.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statement is for reference only.

The company does not assume any legal responsibility, please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.