



BZ-2310 dispersant additive

Composition: Polymers polyester modified compounds

Appearance: yellowish transparent liquid

Active ingredient: 100%

Solvent: None

Application scope: industrial coatings, wood coatings, automobile coatings, etc.

Recommended dosage: Titanium dioxide: 1-3%; Organic pigment: 3-10%; Carbon black: 20-40%;

Pair of full amount: 0.1-0.5%.

Dosage: In order to get the full effect, it is recommended to add it in two periods before and after.

Characteristics and advantages

Excellent dispersion of titanium dioxide, good wetting and dispersion in industrial paint, especially in alkyd resin, excellent viscosity reduction, short dispersion time, no flocculation after uniform dispersion, excellent whiteness of dispersed titanium dioxide.

It has good effect on the wetting and dispersing and liquidity of pigments (such as red, phthalocyanine blue, phthalocyanine green, etc.) of all kinds of color paste.

Package: 25KG non-recycled blue plastic drum.

Before the product is completely empty, the lid should be tightened after use.

Storage: Keep away from heat and light source and keep away from light.

Note: Please carefully evaluate the specific dosage in the coating system before use.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statement is for reference only.

We do not assume any legal responsibility. Please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.