



BZ-2335 Wetting and dispersing additive

Composition: polyurethane polymer compound

Appearance: yellow transparent liquid

Active ingredient: 50%

Solvent: Xylene

Application scope: PU coatings; NC coatings; industrial coatings; automobile coatings

Recommended dosage: 0.1-0.5% of the whole amount; inorganic pigment 1-20%; organic pigment 20-30%; carbon black 50-200%

The resin and solvent should be pre-mixed, and then the additives should be added slowly under stirring until dissolved evenly. The pigments should be added after the additives are added.

Characteristics and advantages:

It has excellent dispersion of pigment and carbon black, improves the color spreading of organic pigment, and effectively reduces the viscosity of high-concentration color paste during grinding.

The viscosity of milled color paste is stable, not easy to return to coarse and flocculation.

Package: 25kg non-recycled blue pail.

Before the container is completely empty, the lid should be tightened after use.

Storage: Keep it away from heat and fire, and keep it away from light.

Precautions: Please evaluate carefully before use, the dosage must be determined after testing.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statements are for reference only.

The company does not assume any legal responsibility, please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.