



BZ-2400 dispersant additive

Composition: polymer block copolymer with pigment-friendly groups

Appearance: light yellow granule powder

Active ingredient: 100%

Application scope: wood coatings, automobile coatings, coil coatings, industrial coatings, printing ink

Recommended dosage: whole amount: 0.1-0.5%; inorganic pigment 2-7%; organic pigment 10-30%; carbon black: 50-100%.

Pre-mixing of resin and solvent, then add the additives slowly under stirring until dissolved evenly, add the pigment after the additives are added.

Characteristics and advantages:

- 1、 It has good effect on the wetting dispersion and fluidity of pigment and carbon black of all kinds of color paste.
- 2、 Improve the transparency of transparent pigment and the covering power of solid color pigment.
- 3、 Applicable to non-resin color paste, improve the color spreading of organic pigments, effectively reduce the viscosity of high concentration color paste in grinding.

Package: 25KG non-recycled barrel.

Before the product is completely empty, the lid should be tightly closed after use.

Storage: Keep it away from heat and light source and keep it away from light.

Caution: Please carefully evaluate the specific dosage in the coating system before use.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statement is for reference only.

The company does not assume any legal responsibility, please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.