



BZ-2431A wetting and dispersing additive

Composition: acrylic block copolymer

Appearance: light yellow transparent liquid

Active ingredient: 100%

Application scope: PU coatings NC coatings Industrial coatings Automotive coatings

Recommended dosage: Total amount: 0.1-0.5%; Inorganic pigment: 1-20%; Organic pigment: 20-30%; Carbon black: 30-80%.

Method: The resin and solvent should be pre-mixed, then add the additives slowly under stirring until dissolved evenly, add the pigment after the additives are added.

Characteristics and advantages:

- 1、Applicable to solvent-based industrial coatings and automotive coatings polymer dispersant.
- 2、It can be applied to resin-free color paste, improve the color spreading of organic pigments, and effectively reduce the viscosity of high concentration color paste during grinding.
- 3、It has wide compatibility with all kinds of resin system and is suitable for dispersing carbon black.

Package: 25KG non-recycled blue pail.

Before the container is completely empty, the lid should be tightened after use.

Storage: Keep away from heat and fire, and keep away from light.

Caution: Please evaluate carefully before use, and the dosage must be determined after testing.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statements are for reference only. The company does not assume any legal responsibility, please test the dosage before use. The company has the right to improve its own products, any changes in its specifications, without prior notice.