



BZ-2432 Universal dispersant additive

Composition: Nonionic compounds

Typical physical data

Appearance: yellowish transparent liquid

Active ingredient: 100%

Solvent: None

Application scope: industrial coatings, wood coatings, automobile coatings

Recommended dosage: Titanium dioxide: 1-3%; Organic pigment: 3-10%; Carbon black: 60%; to the full amount: 0.1-0.5%.

Dosage: In order to get the full effect, it is recommended to add it in two periods before and after.

Characteristics and advantages:

Strong versatility, water and oil universal, good wetting and dispersion of carbon black, all kinds of color paste pigments (such as red, phthalocyanine blue, phthalocyanine green, etc.), excellent viscosity reduction, short dispersion time, no flocculation and return to the roughness of the uniformly dispersed.

Package: 25kg non-recycled blue plastic drum.

Before the product is completely empty, the lid must be tightly closed after use.

Storage: Keep away from heat and light sources and keep away from light.

Caution: Please evaluate carefully before use, and the dosage must be determined after testing.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statements are for reference only. The company does not assume any legal responsibility, please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.