



BZ-2509 wetting and dispersing additive

Composition: special polyurethane polymer

Appearance: light yellow transparent liquid

Active ingredient: 50%

Solvent: PMA

Application scope: UV coatings, wood coatings, industrial coatings, automotive coatings

Recommended dosage: Titanium dioxide: 5-6%; Organic pigment: 10-20%; Carbon black: 10-20%;
Matte powder: 10-30%; to the full amount: 0.1-0.5%.

Usage: In order to get the full effect, it is recommended to add it in two periods before and after.

Characteristics and advantages:

It has good dispersing effect on industrial paints with high filler, especially suitable for wetting and dispersing of matte powder in the system with high matte powder content, it can reduce the viscosity of matte paints with high matte powder content, improve the matting efficiency and make the matting agent well oriented, with excellent anti-sinking effect and improve the storage stability of the paints.

Stabilization of pigments in light-curing printing inks is also applicable to the preparation of pigment concentrates.

Package: 25kg non-recycled blue drum.

Before the product is completely empty, the lid must be tightly closed after use.

Storage: Keep away from heat and light source and keep away from light.

Caution: Please carefully evaluate the relative usage amount before use.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statements are for reference only. We do not assume any legal responsibility. Please test the dosage before use. The company has the right to improve its own products, any changes in its specifications, without prior notice.