



BZ-263 carbon black dispersant additive

Composition: polymer block copolymer with pigment-friendly groups

Appearance: light yellow transparent liquid

Active ingredient: 50%

Solvent: Xylene

Application scope: PU coating NC coating Industrial coating Automobile coating

Recommended dosage: Total amount: 0.1-0.5%; Inorganic pigment: 1-20%; Organic pigment: 20-30%; Carbon black: 30-80%.

Method: The resin and solvent should be premixed, then add the additives slowly under stirring until dissolved evenly, add the pigment after the additives are added.

Characteristics and advantages:

Dispersed carbon black does not return to the coarse, does not thicken, blue phase; dispersion effect is excellent, enhance the transparency of transparent pigments and solid color pigments covering power.

It is suitable for high-grade automobile paint and high-grade special black furniture paint, increasing the gloss of paint and reducing viscosity.

Package: 25KG non-recycled blue pail.

Before the product is completely empty, the lid should be tightly closed after use.

Storage: Keep away from heat and light source and keep away from light.

Caution: Please carefully evaluate the specific dosage in the coating system before use.

The above information is based on the product. Due to the different formulations, production processes and construction conditions of the producers, the above statements are for reference only.

We do not assume any legal responsibility. Please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.