



BZ-4010 wetting and dispersing additive

Composition: Polymer block polymer with pro-pigment group

Appearance: colorless to yellowish transparent liquid

Active ingredient: 50%

Solvent: PMA

Application scope: Industrial coatings, wood coatings, automotive coatings, anti-corrosion coatings, coil coatings.

Recommended dosage: inorganic pigment: 1.0-5.0%; organic pigment: 10-50%; to the full amount: 0.1-0.5%.

Usage: In order to get the full effect, please test the proper dosage before use and add it before grinding.

Characteristics and advantages:

- 1、 Good generality, good compatibility with various resins, outstanding dispersing ability;
- 2, good wettability, reduce grinding time; prevent floating color and blooming, improve pigment coloring power;
- 3、 Excellent dispersion, anti-sinking and arrangement of matte powder, increase the covering power of titanium dioxide, increase the whiteness and improve the gloss of coating system;

Package: 25KG non-recycled blue barrel.

Before the product is not completely empty, the lid must be tightly covered after use.

Storage: Keep it away from heat and light source and keep it away from light.

Note: Please carefully evaluate the specific dosage in the coating system before use.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statement is for reference only.

We do not assume any legal responsibility. Please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.