



## BZ211 wetting and dispersing additive

**Composition:** Polymer compounds

**Appearance:** yellow to brown liquid

**Active ingredient:** 100%

**Solvent:** Xylene

**Application :** Industrial coatings Wood coatings Automotive coatings Anti-corrosion coatings  
Coil coatings

**Recommended dosage:** inorganic pigment: 1.0-3.0%; organic pigment: 3-10%; carbon black:  
15-30%; to the full amount: 0.1-0.5%.

**Usage:** Add before grinding in order to get full effect.

### **Characteristics and advantages:**

1. It has good effect on pigment dispersion and wetting, and effectively prevents pigment flocculation and coarsening phenomenon in paints;
2. It is especially suitable for dispersing inorganic pigment in heavy anti-corrosion paint and industrial paint, metal paint system.

**Package:** 25KG non-recycled blue pail.

Before the product is completely empty, the lid should be tightly closed after use.

**Storage:**Keep it away from heat and light source and keep it away from light.

**Precautions:** Please carefully evaluate the effect on phase solubility and shrinkage before use.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statements are for reference only.

The company does not assume any legal responsibility, please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.