



W-227 ceramic dispersant additive

Composition: Coupling agent dispersant

Appearance: light yellow transparent liquid

Active ingredient: 100%

Solvent: None

Flash point: $\geq 70^{\circ}\text{C}$

Application scope: industrial ceramic coating, gypsum, paper industry, etc;

Recommended dosage: ceramic pigment: 1.0-5.0%; organic pigment: 10-50%; to the full amount: 0.5-2.5%.

Usage: In order to get the full effect, please test the proper dosage before use.

Characteristics and advantages:

Improve the strength of ceramic structure and improve environmental protection, very low foam in the production of ceramic powder; improve the fluidity of ceramic powder, reduce water consumption, can be processed into high solid slurry.

Mainly used for daily-use ceramics, magnetic materials, electronic ceramics and alumina ceramics dispersion; Can be used in combination with other higher or lower binders to adjust stiffness and plasticity;

Package: 25KG non-recycled blue plastic drum.

Before the product is not completely empty, the lid should be tightened after use.

Storage: Keep away from heat and light sources and keep away from light.

Note: Please carefully evaluate the specific dosage in the coating system before use.

The above information is based on the product, due to the producer's formula, production process, construction conditions are different, the above statement is for reference only.

We do not assume any legal responsibility. Please test the dosage before use.

The company has the right to improve its own products, any changes in its specifications, without prior notice.